Technical Specifications for fixed workstation

Processor	Intel Xeon W3-2423(15mb cashe,6 Cores, 121 Threads, 2 .1 Ghz to 4.2 Ghz Turbo,120W)
System Management	No out of band systems management
Memory	64GB,1X64 GB,DDR 5,4800 MHZ,RDIMM ECC Memory
Graphics	NVIDIA T1000,8 GB GDDR6,4 mDP to DP adapters
Storage Configuration	SATA/Upper/Lower Flexbay Assembly included with chassis
Storage Controllers	Integrated Storage Controller
First Internal M.2 SSD	2TB,M.2,Pcie Nvme,SSD,Class 40
VROC	Virtual Raid On CPU software driver
Power Supply	Minimum 750W Chassis(2SATA Flexbay L6)
Chassis Options	Heat sink for 165W or Lower CPU
Power Cord	System Power Cord (india)
Network Card	No Additional Network card selected(integrated NIC included)
Keyboard	Multimedia Wired Keyboard-US International
Mouse	USB Optical Mouse-(EPEAT)Black
E-Star	Energy Star Qualified
EPEAT	EPEAT 2018 Registrated(Gold)
TPM security	Hardware TPM 2.0
Documentation	Document for MUI(English, Khemer, Bahasa Indonesia,Arabic,Spanish)
Placement	Quick start Guide placement Tower
Nvme Raid Configuration	No M.2 NVME Raid
Operating System	Windows11 Pro for Workstations(6 cores)English
Microsoft Office	Activate your Microsoft 365 For A 30days Trial
Warranty	5 Years OEM onsite Comprehensive warranty. Warranty status must be available in OEM website against the supplied model serial no. OEM must |have dedicated toll free support phone no, Email ID's and technical chat support option
General Certification	Energy Star 8.0, RoHS, FCC, CE, UL EPEAT India Registered, ISO 9001:2013, ISO 14001, ISO 27001, ISO 45001 & ISO 50001, Workstation Model should |have Windows and Ubuntu/Redhat/SUSE Linux certification. All the certification must be available in |Public Domain
Manufacturer / OEM Criteria	Minimum 10 Years presence in India. OEM letter confirming that service request would be placed directly with the Desktop OEM for the duration of |warranty period
MONITOR Specification	
MONITOR	4K USB-C Hub Monitor - 32 Inch IPS Monitor
DIAGONAL VIEWING SIZE	800.01 mm (31.5 in.)
COLOR SUPPORT	99% sRGB 1.07 billion colors
CONNECTORS	1x DP 1.4 (in) port (HDCP 1.4, HDCP 2.2) 1x HDMI 2.0 port (HDCP 1.4, HDCP 2.2) 1x USB-C (USB 3.2 Gen 1 (5Gbps) upstream port, Power Delivery up to 90W) 4 x Super speed USB 5Gbps (USB 3.2 Gen1) downstream port 1 x RJ45
ADJUSTABILITY	Height adjustability stand 150 mm Tilt -5° to 21° Swivel -30 to 30° Pivot -90° to 90°

Technical Specifications for fixed workstation

ENVIRONMENTAL COMPLIANCE	ENERGY STAR° certified Monitor EPEAT® registered where applicable. EPEAT registration varies by country. |See www.epeat.net for registration status by country. TCO Certified & TCO Certified Edge. RoHS Compliant. BFR/PVC Free monitor (excluding external cables). Meets NFPA 99 leakage current requirements. " Arsenic-Free glass and Mercury-Free for the panel only.